



ISO-1901:2008 Certified Company



... Water Every where

Water Pump Set



TYPES OF MOTORS

- MONOBLOCK PUMPS
- SUBMERSIBLE PUMPS
- DOMESTIC PUMPS
- ELECTRIC MOTORS
- SHALLOW WELL PUMPS



20% EXTRA ENERGY SAVING



* LATEST PUMP TECHNOLOGY * OVERLOAD PROTECTION * STAINLESS STEEL SHAFT



Save Water **365** days a year.



SELF PRIMING MONOBLOCK PUMP

MODEL NAME:	KW/HP	Max. Current (Amp)	Pipe Size (mm)	Total Head in Meters								
				6	12	18	24	30	36	42	48	
SPL50	0.37/0.5	3.0	25 x 25	2250	1800	1290	900	570				
SPH50	0.37/0.5	3.0	25 x 25	2570	2250	1630	1200	730	190			
SPL100	0.75/1.0	4.0	25 x 25	2770	2400	1800	1290	840	380			
SPH100	0.82/1.1	6.5	25 x 25	3270	3100	2570	2120	1710	1330	950	560	



SUBMERSIBLE PUMPS

SUBMERSIBLE PUMPSET: V⁴ (100 mm) WATER FILLED SINGLE PHASE (220 VOLTS, 50Hz A.C. SUPPLY)

CORA-4

MODEL NO.	MOTOR RATING		STAGE	OUTLET		DISCHARGE IN LPM				
	H.P.	K.W.		INCH	MM	HEAD IN METRES				
						80	68	60	45	30
SPWF408	1.10	0.75	8	1 1/4"	32	24	28	30	35	40
SPWF410	1.10	0.75	10	1 1/4"	32	30	36	39	44	50
SPWF412	1.5	1.1	12	1 1/4"	32	36	43	48	53	60
SPWF415	1.5	1.1	15	1 1/4"	32	45	54	60	66	75

CORA-5

MODEL NO.	MOTOR RATING		STAGE	OUTLET		DISCHARGE IN LPM				
	H.P.	K.W.		INCH	MM	HEAD IN METRES				
						115	100	80	70	45
SPWF508	1.10	0.75	8	1 1/2"	40	24	28	32	35	40
SPWF709	1.5	1.1	12	1 1/2"	40	36	43	48	53	60

CORA-7

MODEL NO.	MOTOR RATING		STAGE	OUTLET		DISCHARGE IN LPM				
	H.P.	K.W.		INCH	MM	HEAD IN METRES				
						140	125	105	100	80
SPWF706	1.10	0.75	6	1 1/2"	40	18	22	24	27	30
SPWF709	1.5	1.1	9	1 1/2"	40	30	34	36	40	44

SUBMERSIBLE PUMPSET: V⁴ (100 mm) OIL FILLED SINGLE PHASE (220 VOLTS, 50Hz A.C. SUPPLY)

CORA-4

MODEL NO.	MOTOR RATING		STAGE	OUTLET		DISCHARGE IN LPM				
	H.P.	K.W.		INCH	MM	HEAD IN METRES				
						80	68	60	45	30
SPOF408	1.10	0.75	8	1 1/4"	32	24	28	30	35	40
SPOF410	1.10	0.75	10	1 1/4"	32	30	36	39	44	50
SPOF412	1.5	1.1	12	1 1/4"	32	36	43	48	53	60
SPOF415	1.5	1.1	15	1 1/4"	32	45	54	60	66	75
SPOF420	2	1.5	20	1 1/4"	32	58	70	78	86	98
SPOF428	3	2.2	28	1 1/4"	32	90	96	107	117	134

CORA-5


MODEL NO.	MOTOR RATING		STAGE	OUTLET		DISCHARGE IN LPM				
	H.P.	K.W.		INCH	MM	HEAD IN METRES				
						115	100	80	70	45
SPOF508	1.10	0.75	8	1 1/2"	40	24	28	32	35	40
SPOF512	1.5	1.1	12	1 1/2"	40	36	43	48	53	60
SPOF515	2	1.5	15	1 1/2"	40	45	54	60	66	75
SPOF520	3	2.2	20	1 1/2"	40	57	63	76	83	95



ELECTRIC MOTORS

Technical Specifications: Single Phase Electric Motors

Particulars	(Single Phase)	(Three Phase)
Power Range	0.5 HP to 5.0 HP	1.0 HP to 15.0 HP
Supply	220 V, 50 Hz	415 V, 50 Hz
Speed	1400 rpm	1400 rpm
Insulation	A/B	A/B/F
Mounting	Foot Mouted	Foot Mouted



Sole Distributor :

S-POWER B.P.E. PVT. LTD.

Kalanki, Kathmandu, Nepal, Tel : 4301451, 4301452,
4280009, 4284229, 4279311, 4279312

Web : www.spowerbpe.com, E - Mail : spowerups@gmail.com

Dealer :

